

Galden[®] HT270

perfluoropolyether

Galden[®] HT PFPE are inert, dielectric and highperformance heat transfer fluids with boiling points ranging from 55°C to 270°C. This range is broader than other fluorinated heat transfer fluids and enables PFPE to be used at end-use temperatures up to 290°C. Syensqo offers a reliable and nonflammable Heat Transfer (HT) media for demanding applications, including:

- Semiconductor
- Chemical
- Pharmaceutical
- Vapor phase heating
- Transformer and super computer cooling
- Recirculating chillers
- Nuclear

General

Material Status	 Commercial: Active 	
Availability	 Africa & Middle East Asia Pacific Europe 	 Latin America North America
Features	Chemical ResistantHigh Density	High Heat Resistance
Forms	• Liquid	

Physical	Typical Value Unit
Average Molecular Weight	1550 amu
Density	1.85 g/cm³
Kinematic Viscosity	14.0 cSt
Solubility	
ofair	26.0 ^{ml} gas/100 ml liquid

of water	<10.0 wppm
Surface Tension	20 dyne/cm
Vapor Pressure	<10E-2 torr

Thermal	Typical Value Unit
Boiling Point	270 °C
Heat of Vaporization - at Boiling Point	15.0 cal/g
Specific Heat Capacity (25°C)	0.23 cal/g/°C

Refractive Index	1.28	ASTM D542
Optical	Typical Value Unit	Test method
Volume Resistance	6*10E15 ohms·cm	
Dielectric Strength - 2.54mm gap	40 kV	
Dielectric Constant	1.94	
Electrical	Typical Value Unit	

Additional Information

Thermal Conductivity (25°C): 0.065 W/m°C Coefficient of Expansion: 0.0011 cm3/cm3°C

Notes

Typical properties: these are not to be construed as specifications.

www.syensqo.com

Safety Data Sheets (SDS) are available by emailing us or contacting your sales representative. Always consult the appropriate SDS before using any of our products.

Neither Syensqo nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this product, related information or its use. Some applications of which Syensqo's products may be proposed to be used are regulated or restricted by applicable laws and regulations or by national or international standards and in some cases by Syensqo's recommendation, including applications of food/feed, water treatment, medical, pharmaceuticals, and personal care. Only products designated as part of the Solviva® family of biomaterials may be considered as candidates for use in implantable medical devices. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infinged. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right.

All trademarks and registered trademarks are property of the companies that comprise the Syensqo or their respective owners.

© 2024 2023 Syensqo. All rights reserved.

